

# ONE TOUCH

## ELECTRIC ATTIC STAIRWAY

THE BEST OF  
**IBS 2015**  
MOST INNOVATIVE  
BUILDING PRODUCT

**AWARD WINNER**

**1<sup>ST</sup>**



- 500 lb. duty rating
- Fully electrically controlled by toggle switch
- Manual opening capability (retraction requires electricity)
- Custom height ranges available from 8' to 16'
- Rough opening lengths of 54" for up to 12' and 60", 61" and 65" from 8' to 16'
- Dual handrails on 25.5" and 30" wide models; single handrail on 22.5"
- .75" thick Flame Stop fire retardant birch panel which meets UL standards for FRS rating
- Meets ANSI standards, ASC A14.9
- Insulated with R-10 aluminum foam board and weather strip to prevent air leakage
- Plugs into 110 vac, 5 amp outlet
- Battery back-up optional
- Completely assembled and ready to install

Model Number	Rough Opening	Ceiling Height
OT22-810	22.5" x 54", 60", 61" or 65"	8' to 10'
OT25-810	25.5" x 54", 60", 61" or 65"	8' to 10'
OT30-810	30" x 54", 60", 61" or 65"	8' to 10'
OT22-1012	22.5" x 54", 60", 61" or 65"	10'1" to 12'
OT25-1012	25.5" x 54", 60", 61" or 65"	10'1" to 12'
OT30-1012	30" x 54", 60", 61" or 65"	10'1" to 12'
OT22-1214	22.5" x 60", 61" or 65"	12'1" to 14'
OT25-1214	25.5" x 60", 61" or 65"	12'1" to 14'
OT30-1214	30" x 60", 61" or 65"	12'1" to 14'
OT22-1416	22.5" x 60", 61" or 65"	14'1" to 16'
OT25-1416	25.5" x 60", 61" or 65"	14'1" to 16'
OT30-1416	30" x 60", 61" or 65"	14'1" to 16'



New Orleans, LA • Columbus, OH  
504-734-1315 • 614-575-9640