

Velocity SRL

GUARDIAN

FALL PROTECTION

Part #	Length	Description
42000	16'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42001	20'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42002	30'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42003	50'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42004	80'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42005	100'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Snap Hook
42006	20'	1" Nylon Webbing w/Carabiner, Swivel Top, & Snap Hook
42008	40'	1" Nylon Webbing w/Carabiner, Swivel Top, & Snap Hook



Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2012, and ANSI A10.32-2012 regulations.

Custom configurations available. Only repairable by manufacturer representative. Contact customer service for details.

Velocity SRL is suitable for the following applications:



Personal Fall Arrest: Velocity SRLs may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Applicable D-ring: Dorsal.

- Part #s 42006, 42007, and 42008: No free fall is permitted. SRL must always be positioned at or above harness dorsal D-ring.

- Part #s 42000, 42001, 42002, 42003, 42004, and 42005: No free fall is permitted, and SRL must always be positioned at or above harness dorsal D-ring. OR, if used in combination with compatible shock absorber extension, maximum 2' free fall, and SRL may be positioned a maximum 2' below harness dorsal D-ring.



Restraint: Velocity SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: stainless steel, galvanized steel, polyester, and glass-filled nylon.

Class B SRL.

Average arrest force: 900 lbs.

Maximum arrest force: 1,800 lbs.

Maximum deceleration distance: 54".

MAXIMUM 1 user per Velocity SRL.

UPC-A Codes: 42000: 672421420004; 42001: 672421420011; 42002: 672421420028; 42003: 672421420035; 42004: 672421420042; 42005: 672421420059; 42006: 672421420066; 42007: 672421420073; 42008: 672421420080