

Diablo Grande SRL

Part #	Length	Description
42009	33'	Diablo Grande w/Galvanized Cable, Swivel Steel Snap Hook, & Steel Carabiner
42010	33'	Diablo Grande for Leading Edge (LE) Work w/Galvanized Cable, Shock Pack, Swivel Steel Snap Hook, & Steel Carabiner
42011	33'	Diablo Grande w/Nylon-Coated Galvanized Cable, Swivel Steel Snap Hook, & Steel Carabiner
42012	33'	Diablo Grande for Leading Edge (LE) Work w/Nylon-Coated Galvanized Cable, Shock Pack, Swivel Steel Snap Hook, & Steel Carabiner

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2012, and ANSI A10.32-2012 regulations.

Custom configurations not available. Repairable **ONLY** by Guardian Fall Protection or authorized repair center. Contact customer service for details.

Diablo Grande SRL is suitable for the following applications:



Personal Fall Arrest: Diablo Grande SRL may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Applicable D-ring: Dorsal.

- Part #s 42010 & 42012: Maximum 2' free fall. SRL may be positioned a maximum 2' below harness dorsal D-ring.

- Part #s 42009 & 42011: No free fall is permitted unless used in combination with Guardian Fall Protection shock absorber extension part # 01205. SRL must always be positioned at or above harness dorsal D-ring, or, if used with shock absorber extension part # 01205, may be positioned a maximum 2' below harness dorsal D-ring.



Restraint: Diablo Grande SRL may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.



WARNING Use of equipment in unintended applications may result in serious injury or death. Maximum 1 attachment per connection point.

Materials: stainless steel, galvanized steel, glass-filled nylon, polyester, and nylon.

Class A SRL.

Average arrest force: 1,350 lbs.

Maximum arrest force: 1,800 lbs.

Maximum deceleration distance: 24".

MAXIMUM 1 user per Diablo Grande SRL.

UPC-A Codes:

42009: 672421420097; 42010: 672421420103; 42011: 672421420110; 42012: 672421420127

