

## Halo Series Harness

Compliant with all applicable OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.11-2014, and ANSI A10.32-2012 regulations.

Custom configurations available. Not repairable. Contact customer service for details.

### Product-Specific Applications:



**Personal Fall Arrest:** Halo Series Harness may be used in Personal Fall Arrest applications as a component of a Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6', unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



**Restraint:** Halo Series Harness may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



**Work Positioning:** Halo Series Harness, configured with side or shoulder D-rings, may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side.



**Rescue/Confined Space:** Halo Series Harness may be used in Rescue/Confined Space applications. Rescue systems function to safely recover a worker from a confined location or after exposed to a fall. There are various configurations of Rescue systems depending on the type of rescue. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. No free fall is permitted. Applicable D-rings: Dorsal, chest, shoulder.



**For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-420 lbs.**

Materials: polyester, nylon, aluminum, and galvanized steel.

Maximum 1 connection per Halo Series Harness.

Always follow all manufacturer's instructions for proper donning and use. Some steps of donning a harness may require assistance from another person.

Upon completely donning a harness, Guardian Fall Protection recommends that another person, with knowledge of the safe and correct use of the harness, inspect to ensure the harness is being worn correctly.

**Contact Guardian Fall Protection for individual harness model part #s, descriptions, and UPC codes.**

**Made in the USA!**