

WIRELESS BACKUP CAMERA SYSTEM WITH CIGARETTE LIGHTER ADAPTOR RVS - 091406

RVS
SYSTEMS
REVERSE WITH CONFIDENCE™

TopTenREVIEWS



Convenience and easy installation is the name of the game with this Digital Wireless Backup Camera System. Its 4.3" Monitor connects straight to the cigarette lighter and comes with a suction cup mount for easy mounting. The monitor comes with optional distance grid lines that can be turned on or off. This system boasts a digital wireless connection which guarantees no interference for up to 70ft so that you get the greatest picture at all times. Its 130° MT9V136 camera comes with 9 infra-red night vision lights which enable you to see in total darkness. The system comes complete with all wires, mounts and connections you will need. With an IP68 weatherproof rating, this camera system is strong and reliable, shock resistant with a 10G vibration rating. It comes with a full year warranty.

WIRELESS BACKUP CAMERA SYSTEM WITH CIGARETTE LIGHTER ADAPTOR RVS - 091406



- COMPLETELY WEATHERPROOF WITH AN IP68 RATING
- 4.3" DIGITAL TFT LCD COLOR MONITOR
- 2.1 MM MT9V136 CAMERA WITH A 130° VIEWING ANGLE
- 1 CHANNEL SYSTEM
- SHOCK RESISTANT WITH A 10G VIBRATION AND 100G IMPACT RATING



MONITOR

TYPE	TFT LCD
SCREEN SIZE	4.3"
DOT RESOLUTION	1440 (H) X 234 (V)
DISPLAY FORMAT/CONTRAST	16:9
DISPLAY BRIGHTNESS	400
VIEWING ANGLE	90° MIN
VIDEO INPUT	1 CHANNEL
VIDEO SOURCE	1VP-P, 75Ω
POWER SUPPLY	DC 12V-24V (+/- 10%)
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	10°C ~ +65° C
VIDEO SYSTEM	AUTO NTSC/PAL
OVERALL DIMENSIONS	5" (L) X 4" (H) X 1" (D)
WEIGHT	400G
VIBRATION RATING	5G
DOT PITCH	154.08 (H) X 86.58 (V)
SYNC SYSTEM	INTERNAL

CAMERA

SENSOR	MT9V136
PICTURE ELEMENTS	250,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	480 TVL
LENS	2.1MM
VIEW ANGLE	130°
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	30 FEET (9 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 12V-24V (+/- 10%)
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 1/60-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND IMPACT RATING	10G / 100G
OPERATING TEMPERATURE	-30°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-50°C ~ +50°C / RH 95% MAX