

Performance

Platform Height 8 ft 2 in. 2.5 m Working Height 14 ft 2 in. 4.32 m Stowed Height 61.4 in. 1.56 m Platform Entry Height 14 in. .36 m Platform Size (W x L) 28.7 in. x 39.3 in. .75 x 1.0 m Overall Vehicle Length 47 in. 1.19 m Overall Vehicle Width 29.5 in. .75 m Gross Vehicle Weight 628 lb 285 kg Platform Capacity 440 lb 200 kg

Standard Specifications

Power Source

Batteries 12V DC AGM Battery
Battery Charger Automatic 110V-240V Charger

Standard Features

- Auto-Lok Wheels on Elevation
- · Non-Marking Wheels
- Rust-Free Tilt-Up Aluminum Platform
- Protective Wall Bumpers
- Tool Tray

- Frame-Mounted Bubble Level
- Service Prop
- · Integrated Fork Pockets
- Detachable Platform Controls with Coil Cable
- Heavy Duty Ultra-Glide Lifting Mast

Accessories & Options

- 110 V or 230V Main Power
- Tilt Alarm with Auto Cut-Out
- Protective Storage Covers



The JLG "1 & 5" Warranty

JLG Industries, Inc. backs its products with its exclusive "1&5" Warranty. We provide coverage on all products for one (1) full year, and cover all specified major structural components for five (5) years. Due to continuous product improvements, we reserve the right to make specification and/or equipment changes without prior notification. This machine meets or exceeds applicable OSHA Regulations in 29 CFR 1910.67, 29 CFR 1926.453, ANSI A92.3-2006, and CSA Standard CSA B354.4, as originally manufactured for intended applications.



JLG Industries, Inc.

1 JLG Drive McConnellsburg, PA 17233-9533 Telephone 717-485-5161 Toll-free in US 877-JLG-LIFT Fax 717-485-6417

www.jlg.com

An Oshkosh Corporation Company