



## LifePoint™ System



The new LifePoint™ ballast weight tie-off is the perfect solution for fall protection when circumstances require non-penetrating versatility. LifePoint™ provides the answer with an easy to set up and quick-move solution.

**Non Penetrating Versatility:** LifePoint™ is a free standing counter weight design that can be placed on flat surfaces with a maximum incline of 5%. Tested and approved for multiple surfaces such as single ply membrane, BUR, concrete, TPO and EDPM. LifePoint™ meets fall-arrest ratings for one person weighing up to 310 lbs (including equipment).

**Modular Design:** LifePoint™ is a modular design makes installation easy. The base is set in place and the individual counterweights are added into position. The center anchor provides safe, simple and rugged use.

**Mobility:** LifePoint™ can be repositioned in a few minutes by one person. With the patented transport cart, LifePoint™ can be moved to a new location quickly and safely by a single person.

**Built to Last:** Whether you transport LifePoint™ job to job or use it as a permanent tie of on your rooftop, with galvanized components LifePoint™ will perform for years.



# LifePoint™ System



Easy mobility: position cart, raise LifePoint™, and move.



Connect lanyard to either Fall-Restraint or Fall-Arrest.



Optional transport cart.

## SPECIFICATIONS

### Base

Dimensions	28.5"x 24"x 13" (LxWxH)
Weight Fully Assembled	960 lbs
Counterweights:	35 lbs each (14 required)
Powder-coated for corrosion resistance	

- Galvanized weight pan with durable rubber bottom.
- Tie-off points for:
  - (1) person Fall Restraint rated
  - AND
  - (1) person Fall Arrest rated

### Transport Cart (optional)

Dimensions	97"x58"x24" (LxWxH)
Weight Fully Assembled	112 lbs

### Safety Ratings

OSHA Spec Certified:	1926.502(d) (16) (iv) Fall Arrest
Fall Arrest Rated:	(1) person
Fall Restraint Rated:	(1) person
Approved Surface Use:	Poured Concrete, EDPM (adhered & loose laid), TPO (adhered & loose laid), BUR (swept)

GARLOCKSAFETY.COM  
Customer Support: (877) 791-4446  
General Number: (763) 694-2624  
Email : info@garlocksafety.com



Distributed by:

