



A Hines Corporation Company

SpeedGuard II Flatbed Fall Protection System



Falls from flatbed trailers cause countless injuries and fatalities. Protect your employees with the SpeedGuard II flatbed protection system. Get the same features as the original SpeedGuard in a more compact, easy-to-install and transport package.

Safety is Job 1: At 10 ft (height of a worker standing on a 48" flatbed) up to 720 ft. lbs of energy and 4300 lbs of impact force are generated. This is more than enough to cause severe injury or fatality. Climbing on and off the flatbed also puts your employees at risk. The SpeedGuard II eliminates both these hazards from the workplace.

New SpeedKart: Allows quick and easy transport. With large tires, the SpeedKart can be moved by one person over uneven terrain. The unique handle/brake keeps the cart stationary during loading and unloading.

E-Z Mount Ladder: designed to fit in standard flatbed side pockets. At only 36 lbs it is easily placed. When combined with the SpeedGuard Gate safe access to the flatbed is assured for installing load binders and tarping equipment.

Flexibility: The SpeedGuard system is designed to fit in standard pockets and includes all components needed to protect trailers up to 48 ft long. (order extension kit to protect trailers up to 53 ft.) With installation in less than 10 minutes SpeedGuard makes safety easy.



www.garlocksafety.com

SpeedGuard II Features:



Install Ladder



Install Pockets



Install Railings



Safely Climb Up



Safely Work

SPECIFICATIONS

Cart Dimensions:

Length: 116"

Width: 45"

Height: 75"

Weight: 903 lbs fully loaded (435 lbs SpeedKart only)

Safety Ratings: Meets applicable OSHA 1926.502 standards for fall protection

FULL PRODUCT LINE



Distributed By:

A
HINES
CORPORATION
COMPANY



2601 Niagara Lane North Plymouth, MN 55447
(877) 791-4446 / P: (763) 694-2624 / F: (800) 820-3268
www.garlocksafety.com