

BACKUP CAMERA SYSTEM TWO CAMERA SETUP



**Industrial
Products®**



NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION

This 2 camera system is complete with a crystal clear 7" DIGITAL LED COLOR monitor with distance grid lines and mirror image capability, a power harness, two (2) 130° CCD cameras with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry), and comes with a full year warranty.

System can be upgraded to the Quad View Monitor where a split screen (to view two cameras at the same time) is an option.

BACKUP CAMERA SYSTEM TWO CAMERA SETUP



A Safe Fleet Brand

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- 7" DIGITAL LED COLOR MONITOR WITH REMOVABLE SUNSHADE
- 2.5 MM COLOR CCD CAMERAS WITH A 130° VIEWING ANGLE
- 3 CHANNEL POWER HARNESS ALLOWING YOU TO CONNECT AN ADDITIONAL CAMERA
- SHOCK RESISTANT WITH A 20G VIBRATION AND 100G IMPACT RATING



NOTE: DETAILS MAY CHANGE
BASED ON ITEM CONFIGURATION



MONITOR

| | |
|-----------------------|-----------------------------|
| PANEL SIZE | 7" LED DIGITAL PANEL |
| DOT RESOLUTION | 800 X 3 (RGB) X 480 |
| SCREEN MODE | 16:9 |
| CONTRAST RATIO | 500:1:00 |
| DISPLAY BRIGHTNESS | 400CD/m ² |
| FIELD OF VIEW | U:50° D:60° L/R:70° |
| VIDEO INPUT | 3 CHANNEL CVBS |
| VIDEO SOURCE | 1VP-P, 75Ω |
| POWER SUPPLY | DC 9V-32V |
| AUDIO OUTPUT | 0.5W |
| OPERATING TEMPERATURE | -20°C ~ +70° C |
| VIDEO SYSTEM | AUTO NTSC/PAL |
| OVERALL DIMENSIONS | 7" (L) X 5.25" (H) X 1" (D) |
| WEIGHT | 400G |
| IMPACT RATING | 5G |
| DOT PITCH | 0.1926 (H) X 0.1710(V) |
| SYNC SYSTEM | INTERNAL |

CAMERA

| | |
|----------------------------|---|
| SENSOR | 1/3" SHARP® COLOR CCD |
| PICTURE ELEMENTS | 410,000 PIXELS |
| GAMMA CORRECTION | R=0.45 TO 1.0 |
| IMAGE SENSOR | 620 TV LINES, PAL: 752(H) X 582 (V), NTSC: 811(H) X 507 (V) |
| LENS | 2.5MM |
| VIEW ANGLE | 130° |
| WATERPROOF RATING | IP69K |
| SYNC SYSTEM | INTERNAL SYNCHRONIZATION |
| INFRA-RED DISTANCE | 50 FEET (18 INFRARED) |
| USABLE ILLUMINATION | 0 LUX (IR ON) |
| POWER SOURCE | DC 9V-32V |
| S/N RATIO | MORE THAN 48DB |
| ELECTRONIC IRIS | 1/50, 160-1/100,000SEC |
| VIDEO OUTPUT | 1VP - P, 75 Ω |
| IR SWITCH CONTROL | ACDS AUTOMATIC CONTROL |
| VIBRATION AND SHOCK RATING | 20G / 100G |
| OPERATING TEMPERATURE | -40°C ~ +70°C / RH 95% MAX |
| STORAGE TEMPERATURE | -40°C ~ +85°C / RH 95% MAX |
| NET WEIGHT | 220Z |