



6' Compact Retractable

Lightweight safety in the palm of your hand



Quick locking action for low clearance applications



Combine two units for a twin leg, 100% tie-off solution



Lightweight, compact, durable



Steel rebar hook for form work

NEW

Class A <24" arrest distance & <900 lb arrest force



6' Compact Retractable



Carabiner
Connects device to harness in single leg application

Swivel Anchor Loop
Limits lifeline twisting for smooth operation

Impact-Resistant Housing
high-strength housing maximizes durability

Shock Absorber
integrated impact absorber

3600lb Gate
Twinleg Carabiner Adaptor connects through webbing under harness D-ring



- Quick Locking Action for low clearance applications
- Meets ANSI z359.14 CLASS A <24" arrest distance requirement while keeping average arrest force <900 lbs.
- Extremely compact and lightweight at less than 2.5 lbs
- 310 lb rated capacity
- Maximum arrest distance of 24"
- Achieve 100% tie-off configuration by making a twin-leg self-retracting lifeline.
- SR option for working with Concrete Forms



R430006



R431006



R43006-SR



R430006-R



R431006-R



R431006-SR

*not for use in leading edge applications

Model#	Lifeline Length	LifeLine Material	Housing Material	Lifeline Connector	Anchorage Connector	Weight	Standard Compliance
R430006	6'	Dyneema/ Polyester	Impact Resistant Nylon	Snap Hook	Carabiner	2.3 lbs.	ANSI z359.14, Class A (24") OSHA 1910 & 1926
R430006-R	6'			Al Rebar	Carabiner	2.5 lbs.	
R430006-SR	6'			Form Hook	Carabiner	5.5 lbs.	
R431006	Twinleg 6'			Snap Hook	Twinleg Carabiner	5.5 lbs.	
R431006-R	Twinleg 6'			Al Rebar	Twinleg Carabiner	5.7 lbs.	
R431006-SR	Twinleg 6'			Form Hook	Twinleg Carabiner	11.7 lbs.	



Industrial Products[®]

5717 Salmen Street New Orleans, LA 70123

www.industrialproducts.com | sales@industrialproducts.com | 888-243-3339