



# SRL

Serial Number: \_\_\_\_\_

- Pass
- Remove From Service

Inspector Name: \_\_\_\_\_ Inspection Date: \_\_\_\_\_

Model Number: \_\_\_\_\_ Manufacture Date: \_\_\_\_\_ Date of First Use: \_\_\_\_\_

For more information, please see user instructions sent with the product at the time of shipment.

### Operation

The lifeline must fully extract and retract smoothly without any slack being created upon controlled retraction.

- Not Retracting     Not Extracting
- Does Not Extract / Retract Smoothly - Slack in Lanyard

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Locking Mechanism

Check the operation of the unit by pulling smoothly on the lifeline, then pull sharply on the lifeline to engage the locking mechanism. Unit must not slip when locked.

- Not Locking     Slips when Locked

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Webbing

To inspect webbing, bend a portion of the webbing 6-8 inches into an upsidedown 'U' shape. Continue along all webbing inspecting for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, pulled or broken stitches, or other signs of wear and damage. Adjust all keepers, buckles, padding and D-ring to inspect webbing hidden by these components.

- Tears     Cuts     Fraying     Abrasion
- Discoloration     Burns     Holes     Mold

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Stitching

Sewn terminations must be secure, complete, and not visibly damaged.

- Broken     Missing     Load Indicator Warning

- Pass
- Remove From Service

Comments: \_\_\_\_\_

# Inspection Sheet





# SRL

### Housing / Casing

Housing or casing must be free from cracks, distortion or any other damage.

- Cracks
- Distortion

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Cable

Cable must be inspected for kinks, broken strands, corrosion, abrasion, or other signs of wear and damage. Swaged terminations should be secure with the thimble tight, and not visibly damaged.

- Kinks
- Corrosion
- Abrasion
- Separation of Wire
- Chemical Attack
- Broken Wire
- Alteration
- Excessive Heating

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Rope

Rope must be inspected for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, or other signs of wear and damage.

- Tears
- Cuts
- Fraying
- Abrasion
- Mold
- Discoloration
- Burns
- Holes
- Unsplicing
- Knots

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Snap hooks / Carabiners

Snap hooks and carabiners on product must be able to self-close and lock. All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Does Not Close
- Cracks
- Deformation
- Corrosion
- Does Not Lock
- Sharp Edges
- Alteration
- Load Indicator Warning

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Hardware

All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Cracks
- Sharp Edges
- Deformation
- Corrosion
- Chemical Attack
- Wear
- Alteration
- Excessive Heating

- Pass
- Remove From Service

Comments: \_\_\_\_\_

### Labels

All markings must be legible and attached to the product.

- Illegible
- Missing

- Pass
- Remove From Service

Comments: \_\_\_\_\_

# Inspection Sheet

