



# Harness

Serial Number: \_\_\_\_\_

- Pass
- Remove From Service

Inspector Name: \_\_\_\_\_ Inspection Date: \_\_\_\_\_

Model Number: \_\_\_\_\_ Manufacture Date: \_\_\_\_\_ Date of First Use: \_\_\_\_\_

For more information, please see user instructions sent with the product at the time of shipment.

## Webbing

To inspect webbing, bend a portion of the webbing 6-8 inches into an upsidedown 'U' shape. Continue along all webbing inspecting for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, pulled or broken stitches, or other signs of wear and damage. Adjust all keepers, buckles, padding and D-ring to inspect webbing hidden by these components.

- Tears
- Cuts
- Fraying
- Abrasion
- Pass
- Remove From Service
- Discoloration
- Burns
- Holes
- Mold

Comments: \_\_\_\_\_

## Hardware/Buckles/Grommets

All hardware must be free of cracks, sharp edges, deformation, corrosion, or any evidence of defect.

- Cracks
- Sharp Edges
- Deformation
- Corrosion
- Pass
- Remove From Service
- Chemical Attack
- Wear
- Alteration
- Excessive Heating

Comments: \_\_\_\_\_

## Stitching

Sewn terminations must be secure, complete, and not visibly damaged.

- Broken
- Missing
- Load Indicator Warning
- Pass
- Remove From Service

Comments: \_\_\_\_\_

## Labels

All markings must be legible and attached to the product.

- Illegible
- Missing
- Pass
- Remove From Service

Comments: \_\_\_\_\_

# Inspection Sheet

