

# **HANDLE-IT®** SA Series



Full Set of Functions & Options

Power Pre-Stretch Carriage

200 + pallets per charge

Technical Specifications	
Wrap Height	94"
Battery Charge	1 Ph+N 50/60 Hz
Max Daily Workload	350 cycles
Powered by	2 x 12v AGM batteries
Weight Capacity	unlimited
Pre-Stretch	250% Powered
Power Supply	110/240 VAC
Total Machine Footprint	72" x 30" x 99"
Machine Weight	900 lbs
Drive Speed	1.6 - 4.4 feet per sec.

Part Number: SWM-MR-3000

#### Handle-It® Model 3000

The Handle-It® *Model 3000* offers top-of-the-line functions and features at a great price. It is ideal for those who are looking for an efficient machine capable of handling high volumes of pallets per day. This machine gives you the flexibility to wrap a wide variety of pallet sizes and weights and is portable.

Standard features on the model 3000 include 250% powered pre-stretch, user-friendly PLC touch screen control panel, braked carriage, and many other elements cleverly designed to make this unit a must-have in any facility looking to improve and streamline their packaging operations.



## **HANDLE-IT®**

# Semi-Automatic Stretch Wrapper

#### **Product Specifications**

- Electronic printed circuit board for the management of the cycle
- Frequency controller for carriage speed adjustment (speed going up and speed going down can be set differently)
- 250% Power pre-stretch film carriage
- Electromagnetic brake for film stretching
- Photocell for pallet height detection
- Safety stop at the base of machine
- Power board ip54
- Main parameters protected by password
- Main parameters adjustable by the control panel: cycle selection, bottom wraps, top wraps, rotation speed, carriage speed going up, carriage speed going down, film tension, photocell delay, starting height
- 20 programs can be saved by the customer
- Acoustic warning at the cycle beginning and stop
- Battery charge monitoring and warning message on the display when the battery is low
- Autodiagnostic
- Advanced battery charger with efficiency > 85%, charging process fully controlled by
  microprocessor, automatic reset after connecting a new battery, protection against polarity
  inversion and short circuits, autodiagnostic, compensation of the voltage drop on the battery
  cables, normally closed power contact
- 2 year limited warranty



### **Available Options**

- Photocell for Dark Loads
- Stop at home position
- Double Wheel
- Auto cut-off
- 118" Max Wrap Height
- Spare battery kits









