



# A216400

## Bull Ring Anchorage Connector

### FEATURES

- Minimum Breaking Strength (MBS): 5,000 lb
- 2 inch connector ring
- Fastening holes for nails and lag screws
- Meets ANSI Z359.18-2017
- Meets OSHA 1910.140 and 1926.502



### SPECIFICATIONS

| Model No. | Material          | Length        | Width        | Connection Size | Hole Diameter                             | Minimum Breaking Strength (MBS) | Approx. Weight   | Compliance Standards                  |
|-----------|-------------------|---------------|--------------|-----------------|-------------------------------------------|---------------------------------|------------------|---------------------------------------|
| A216400   | Zinc Plated Steel | 9 in (229 mm) | 3 in (76 mm) | 2 in (51 mm)    | 5/16 in (8 mm) Lag<br>3/16 in (5 mm) Nail | 5,000 lbs (22.2 kN)             | 2.0 lbs (0.9 kg) | ANSI Z359.18-2017<br>OSHA 1910 & 1926 |

\*See User Instructions for more information.

**⚠ WARNING:** Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

## Technical Data Sheet

WernerCo Corporate Headquarters: 555 Pierce Road, Suite 300, Itasca, IL 60143

TEL: 888-523-3370 FAX: (724) 588-0315 [www.wernerco.com](http://www.wernerco.com)