




# H12300X

## Blue Armor Full Body Harness

### FEATURES

- Built in Relief Handles assist user to get into the Chair in the Air after fall arrest
- 1¾ polyester WebAlert™ inspectable webbing
- Lightweight form fitting polyester back pad with breathable compression interior
- Meets requirements of ANSI Z359.11



## Blue Armor™

### INSPECTABLE HARNESS



### SPECIFICATIONS

Model No.	Size	D-Rings	D-Ring Material	Chest Connection	Leg Connection	Capacity	Approx. Weight	Compliance Standards
H123001	Small	Back; Front	Steel	Quick Connect	Quick Connect	425 lbs (193 kg)	3.9 lbs (1.8 kg)	ANSI Z359.11- 2021 OSHA 29 CFR 1910 & 1926
H123002	Medium/Large	Back; Front	Steel	Quick Connect	Quick Connect	425 lbs (193 kg)	3.9 lbs (1.8 kg)	ANSI Z359.11- 2021 OSHA 29 CFR 1910 & 1926
H123004	X-Large	Back; Front	Steel	Quick Connect	Quick Connect	425 lbs (193 kg)	4.1 lbs (1.9 kg)	ANSI Z359.11- 2021 OSHA 29 CFR 1910 & 1926
H123005	XX-Large	Back; Front	Steel	Quick Connect	Quick Connect	425 lbs (193 kg)	4.1 lbs (1.9 kg)	ANSI Z359.11- 2021 OSHA 29 CFR 1910 & 1926

\*See User Instructions for more information.

**⚠ WARNING:** Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

# Technical Data Sheet