



R433006LE

Bantam Self Retracting Lifeline with Leading Edge Capability

FEATURES

- 6 foot working range
- 1 inch Kevlar® and UHMWPE webbing
- Thermoplastic housing
- Swivel top with steel web connector
- Aluminum rebar hook has a gate opening of 2 ½ inches (63.5 mm)
- Steel form hook has a gate opening of 2 ¾ inches (61 mm)
- Snap hook, rebar hook and form hook are self-locking with a minimum tensile break strength of 5,000 pounds and a 3,600 pound gate rating

SPECIFICATIONS

Model No.	Lifeline Connector	(A)	(B)	Aprox. Weight
R433006LE	Steel Snap Hook	34 ½ in (851 mm)	9 ½ in (232 mm)	6.15 lbs (2.79 kg)
R433006LE-R	Aluminum Rebar Hook	37 in (940 mm)	9 ½ in (232 mm)	7.15 lbs (3.24 kg)
R433006LE-SF	Steel Form Hook	37 ¼ in (946 mm)	9 ½ in (232 mm)	6.96 lbs (3.16 kg)



OVERHEAD USE NON LEADING EDGE APPLICATIONS

Meets	Maximum Arrest Distance	Average Arrest Force	Maximum Arrest Force	Free Fall Limit	Capacity
ANSI Z359.14-2021 CLASS 2	24 in (610 mm)	1,350 lbf (6 kN)	1,800 lbf (8 kN)	24 in (610 mm)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.140 & 1926.502	42 in (1067 mm)	N/A	1,800 lbf (8 kN)	24 in (610 mm)	400 lbs (181 kg)



COMPLIANCE STANDARDS

LEADING EDGE USE APPLICATIONS

Meets	Free Fall Limit	Maximum Arrest Force	Average Arrest Force	Minimum Setback Distance	Clearance requirement when falling over edge	Capacity
ANSI Z359.14-2021 CLASS 2	6 ft (1.8 m)	1,800 lbf (8 kN)	900 lbf (4 kN)	2 ft (0.6 m)	17 ft (5.1 m)	130 - 310 lbs (59 - 141 kg)
OSHA 29 CFR 1910.140/1926.502	6 ft (1.8 m)	1,800 lbf (8 kN)	N/A	2 ft (0.6 m)	17 ft (5.1 m)	310 lbs (141 kg)



*See User Instructions for more information.

⚠ WARNING: Compliant fall protection equipment must only be used as it was designed and adhere to the hierarchy of controls as discussed in ANSI Z359.2. Users MUST read and follow all user instructions provided with the product. Before using a fall arrest system, users must be trained in the safe use of the system, as required by OSHA 29 CFR 1910.30 and 1926.503, or local safety regulations. Misuse or failure to heed these warnings and instructions may result in injury or even death.

WORK SAFE! WORK SMART!

Technical Data Sheet