


SUPER SIMPLEX DISAPPEARING STAIRWAY WITH DEEP BOX FRAME

(USE THIS DRAWING FOR CEILING HEIGHTS FROM 12'-1" TO 13' -6")


ONE INCH FLANGE
ALL AROUND
TOP & BOTTOM





22-1/2" x 72" ROUGH OPENING
IN CEILING (AND FLOOR ABOVE)

SPECIAL DEEP BOX FRAME

1/8" STEEL, TO CONTAIN ALUMINUM SUPER SIMPLEX FOLDING STAIRWAY CUT FOR EXACT FINISHED CEILING HEIGHT. THIS FRAME, WITH FACTORY INSTALLED BUILT-IN TREADS, PROVIDES STEPS FROM THE DROPPED-CEILING LINE TO THE UPPER FLOOR.




FRAME LADDER DETAIL



OPTIONS

- ☐ 2 HOUR FIRE RATED ASSEMBLY
- ☐ LOCK ON DOOR PANEL

NOT TO SCALE



LOAD RATING - 500 LBS.

LADDER LEGEND

- 1. STEEL PIANO DOOR HINGE
- 2. DOUBLE SPRING ACTION
- 3. SIDE RUNNER 5" ALUM.
- 4. BATTEN 1/8" ALUM.
- 5. DOOR PANEL 1/8" ALUM.
- 6. STEEL BOX FRAME
- 7. TREAD (SERRATED ALUM.)
- 8. HANDRAIL BOTH SIDES
- 9. EXTRA HEAVY OPERATING ARM
- 10. ADJUSTABLE FOOT
- 11. MIDDLE SECTION
- 12. BOTTOM SECTION
- 13. FOLD-ASSIST

S-162-BD-22.5

NOTES

DIMENSIONS ON THIS DRAWING PERTAIN ONLY TO CEILING HEIGHTS OVER 12'-0".
MANUFACTURER RECOMMENDS 2 PEOPLE TO OPEN/CLOSE SHIPS COMPLETELY ASSEMBLED AS ONE UNIT

DWG. CHECK

BUILT BY:

CHECKED BY:

ARCH'T OR ENG'R.

PURCHASE ORDER

DRAWN BY:

JBR

PROJECT

WORK ORDER

DATE 7/27/09

PURCHASER

MODEL#

SS/AL-

PRECISION REP

SERIAL#

QTY.